

CITIZENS PROPERTY INSURANCE CORPORATION
**FLORIDA BUILDING CODE WALL & ROOFING MITIGATION VERIFICATION
AFFIDAVIT**

Applicant(s): _____ **Policy No:** _____

Property Address: _____

Installation Date: _____ / _____ / _____

Specify the type of mitigation device(s) installed:

<input type="checkbox"/> Roof Coverings <ul style="list-style-type: none"><input type="checkbox"/> FBC Equivalent Asphalt roof coverings installed in accordance with ASTM D 3161 (modified for 110 mph) or Miami Dade County PA 107-95.<input type="checkbox"/> Non-FBC Equivalent Asphalt roof shingles not meeting requirements listed above for FBC Equivalent and all other roof covering types.<input type="checkbox"/> Reinforced Concrete Roof Deck A roof structure composed of cast-in-place or pre-cast structural concrete designed to be self-supporting and integrally attached to wall/support system.

<input type="checkbox"/> Roof Shape <ul style="list-style-type: none"><input type="checkbox"/> Hip Roof having sloping ends and sloping sides down to the eaves line.<input type="checkbox"/> Other All other roof shapes except hip (i.e. Flat, Gable, Gambrel, etc.).

<input type="checkbox"/> Secondary Water Resistance <ul style="list-style-type: none"><input type="checkbox"/> Underlayment A self-adhering polymer modified bitumen roofing underlayment (thin rubber sheets with peel and stick underside located beneath the roof covering and normal felt underlayment) with a minimum width of 6" meeting the requirements of ASTM D 1970 installed over all plywood/OSB joints to protect from water intrusion. All secondary water resistance products must be installed per the manufacturer's recommendations. Roofing felt or similar paper based products are not acceptable for secondary water resistance.<input type="checkbox"/> Foamed Adhesive A foamed polyurethane sheathing adhesive applied over all joints in the roof sheathing to protect interior from water intrusion.
--

<input type="checkbox"/> Roof-Wall Connection <ul style="list-style-type: none"><input type="checkbox"/> Toe-Nail Rafter/truss anchored to top plate of wall using nails driven at an angle through the rafter/truss and attached to the top plate of the wall.<input type="checkbox"/> Clips Metal clips installed on each truss/rafter that attach to the side only of the truss/rafter member and to the wall frame. Metal clip should be free of severe corrosion, have a minimum of 3 nails into the truss/rafter and 3 nails into the wall.<input type="checkbox"/> Single Wraps Metal straps installed on each truss/rafter that wrap over the top of the truss/rafter and attach to the wall frame in one location. Metal strap should be free of severe corrosion, have a minimum of 3 nails into the truss/rafter and 3 nails into the wall.<input type="checkbox"/> Double Wraps Metal straps installed on each truss/rafter that wrap over the top of the truss/rafter and attach to the wall frame in two locations. Metal strap should be free of severe corrosion, have a minimum of 3 nails into the truss/rafter and 3 nails into the wall at each location.

CITIZENS PROPERTY INSURANCE CORPORATION
FLORIDA BUILDING CODE WALL & ROOFING MITIGATION VERIFICATION AFFIDAVIT

Roof Deck Attachments

Attachment A

Plywood/OSB roof sheathing attached to roof trusses/rafters by 6 penny nails (2" x 0.131" diameter) or greater which are properly spaced at a maximum of 6" along the edge and 12" in the field on 24" truss/rafter spacing.

Or

Batten decking of Skipped decking (typically used on roof decks supporting wood shakes or wood shingles).

Or

Any system of screws, nails, adhesives, other roof deck fastening systems or truss/rafter spacing that has an equivalent mean uplift resistance of 55 pounds per square foot or more as evidenced by laboratory uplift tests on full size sheets of plywood/OSB.

Attachment B

Plywood/OSB roof sheathing with a minimum thickness of 1/2" attached to roof trusses/rafters by 8 penny (2.5" x 0.131" diameter) nails or greater which are properly spaced at a maximum of 6" along the edge and 12" in the field on 24" truss/rafter spacing.

Or

Any system of screws, nails, adhesives, other roof deck fastening systems or truss/rafter spacing that has an equivalent mean uplift resistance of 103 pounds per square foot or more as evidenced by laboratory uplift tests on full size sheets of plywood/OSB.

Attachment C

Plywood/OSB sheathing with a minimum thickness of 1/2" attached to roof trusses/rafters by 8d (2.5" x 0.131" diameter) nails which are properly spaced at a maximum of 6" along the edge and 6" in the field on 24" truss/rafter spacing.

Or

Dimensional Lumber or Tongue & Groove deck roof composed of 3/4" thick boards with nominal widths of 4" or more.

Or

Any system of screws, nails, adhesives, other roof deck fastening systems or truss/rafter spacing that has an equivalent mean uplift resistance of 182 pounds per square foot or more as evidenced by laboratory uplift tests on full size sheets of plywood/OSB.

Certification of Wind Speed Design of Structure when above the basic wind speed design of location of structure.

I hereby certify that the building or unit at the address indicated above is designed and mitigated to the Florida Building Code (FBC) **WIND DESIGN SPEED** of (Check One): **≥110** or **≥120**

Certification below for purposes of **WIND SPEED DESIGN** above does not require personal inspection of the premises.

CERTIFICATION

I certify that I am (CHECK ONE OF THE FOLLOWING):

a resident **Licensed General, Residential, or Building Contractor**, a **Licensed Building Inspector**,

a **Registered Architect**, an **Engineer** in the State of Florida, or a **Building Code Official** (who is duly authorized by the State of Florida or its county's municipalities to verify building code compliance).

I also certify that I personally inspected the premises at the Location Address listed above on the date of this Affidavit. In my professional opinion, based on my knowledge, information and belief, I certify that the above statements are true and correct.

This Affidavit and the information set forth in it are provided solely for the purpose of verifying that certain structural or physical characteristics exist at the Location Address listed above and for the purpose of permitting the Named Insured to receive a property insurance premium discount on insurance provided by Citizens Property Insurance Corporation and for no other purpose. The undersigned does not make a health or safety certification or warranty, express or implied, of any kind, and nothing in this Affidavit shall be construed to impose on the undersigned or on any entity to which the undersigned is affiliated any liability or obligation of any nature to the named insured or to any other person or entity.

Name of Company: _____ **License #** _____

Date: _____ **Phone:** _____

Signature: _____

Applicant's Signature: _____ **Date:** _____

Citizens reserves the right to confirm all information contained in this form via a survey of the risk.

"Any person who knowingly and with intent to injure, defraud, or deceive any insurer files a statement of claim or an application containing any false, incomplete, or misleading information is guilty of a felony of the third degree."